

FilTek[®] stainless steel drinking fountain

FilTek[®] offers a broad line of stainless steel non-refrigerated drinking fountains for connection to the water supply through Fabri-Technic UV water sterilizer. Remote water chiller can follow in option.

This range is standardized with a fabrication of type 304 stainless steel that is polished to a mirror finish. Bubbler contains a built-in pressure regulator to deliver smooth, steady flow at supply pressures ranged from 20 to 125 psi.

The waterway systems in all these fountains are constructed with copper components and lead-free materials. A lead-free brazing alloy is used on all joints. They meet UL and CSA requirements as well as all sanitary codes.

Other detailed specifications for individual models are stated overleaf.

Physical Dimensions

Model	Height	Width	Depth	Extended from Wall	Recessed from Wall	Net Weight
FT100	235	432	334	334	—	5.5
FT110	276	330	339	339	—	4.5
FT110R	244	368	409	409	—	7.7
FT120	376	330	333	333	—	2.7
FT130	705	440	241	241	—	5.7
FT140	178	330	483	483	—	5.5
FT140PM	178	330	483	483	—	5.5
FT140R	244	368	551	551	—	8.6
FT200	705	440	330	241	89	5.9
FT211	889	457	279	25	267	12.7
FT300	102	337	267	—	—	1.8
FT300R	89	356	356	—	—	4.1
FT400	914	343	343	—	—	6.8
FT500	914	356	289	—	—	12.7

All dimensions in mm and weights in kg.



FT-400



FT-500



FT-130



FT-211



FT-200



FT-110



FT-100



FT-120



FT-300



FT-140PM



FT-140



FT-300R



FT-110R



FT-140R